

	90R	90KR	90KRE
	90 Series	Key Removable	Electrified Key Removable
			
Easily Removed	•	•	•
Removal Method	6 screws	Keyed Cylinder	Keyed Cylinder
Standard Mullion	90R	90KR	90KRE
Available Fire Rated	F90R	F90KR	
Available Hurricane Rated	H90R		
Available Fire and Hurricane Rated	FH90R		
Cylinder required		•	•
Cylinder included		Optional Rim Cylinder	Optional Rim Cylinder
Optional cylinder or SFIC Housing available		•	•
Lengths Available	7 and 8 Foot	7, 8 and 10 Foot	7 and 8 Foot
Fire Rated Lengths	7 and 8 Foot	7 and 8 Foot	n/a
All mounting material included	•	•	•
Listings and Approvals (Hurricane)	NOA 13-0717.13 NOA 13-0617.22		
Listings and Approvals (Fire)	UL and Warnock Hersey listed for 3 hour fire rated pairs of doors up to 8' x 8'	UL and Warnock Hersey listed for 3 hour fire rated pairs of doors up to 8' x 8'	UL and Warnock Hersey listed for 3 hour fire rated pairs of doors up to 8' x 8'
Listings and Approvals (Fire)	WHI labeled for use with other manufacturers' fire exit hardware	WHI labeled for use with other manufacturers' fire exit hardware	WHI labeled for use with other manufacturers' fire exit hardware
Retrofit compatible	•	•	•
Color/s available	Standard primer gray	Standard primer gray	Standard primer gray
Material	1/4" thick, 2" x 3" steel mullion tube	11 gauge, 2" x 3" steel mullion tube	11 gauge, 2" x 3" steel mullion tube
Warranty	10 Years	10 Years	10 Years