



# DS5500 Series



DS5500 Series  
DS5500-P Series - Portable



**Standard Unit**



**Portable Unit**

\* Dimensions are approximate

**Measures:**

- Height: 37" (939.8mm)
- Width: 20.125" (511.1mm)
- Depth: 8.187" (207.2mm)
- Arm Length: 14.500" (368.3mm)

*Dimensions are subject to change without notice*

**Options:**

- Bidirectional key overrides
- Daylight visible indicator lights
- 8 digit key resettable LCD counter with seven year lithium battery
- Additional options available on request


**Product Features:**

**Materials and Finishes available**

**in your choice of:**

- Lid: 304 stainless steel /No. 4 satin finish
- Cabinet: Your choice of designer powder coat colors to match any décor. Black is standard.

**Standard powder coating color selections:**



Additional colors are available and can be quoted upon request.

**Design & Construction:**

- Designed for secure and reliable operation with aesthetics in mind
- Cabinet is constructed with rigid (7 gauge) carbon steel
- Cover is constructed with (14 gauge) 304 stainless steel, No. 4 satin finish
- Arm assembly constructed with 1 5/16" (33mm) diameter, (12 gauge) stainless steel
- Hub 4 1/2" (114mm) o.d. also made from stainless

**Electrical Specifications:**

Input voltage: 100-240 VAC

Input current: 1.3 - .55 A

Frequency: 50/60 Hz

Storage Temperature: -40 to 158°F

Operating Temperature: -4 to 131°F  
(cold weather package available)

Operating voltage: 24VDC

Operating current: 1.2 A (typical)

**Standards and Codes:**

Austenitic stainless steel:ASTM

A240, A249, A276

Hot rolled steel:

AISI C-1020, AISI C-1018

Hot dipped galvanizing:

ASTM A-143, ASTM A-153-80

Stainless steel fasteners:

ASTM A-320

American Welding Society (AWS)

Standard D 1.1

**Matching ADA Gate available**

(see model DS5000-ADA information)

**Warranty:**

Units are warranted against defects in materials and workmanship for a period of one year from date of invoice.